



Water options



Chilled Ambient Hot Sparkling

Configuration



Countertop Floorstanding

borg &
overström

b3

Recommended environment



Offices Hospitality Healthcare Education Leisure

Number of users




6-10 11-25

b3 Models

Reservoir, Floorstanding, Chilled, Ambient— 104910
Reservoir, Floorstanding, Chilled, Hot— 104110
Reservoir, Countertop, Chilled, Ambient— 104210
Reservoir, Countertop, Chilled, Hot— 104310
Direct Chill, Floorstanding, Chilled, Ambient— 104410
Direct Chill, Countertop, Chilled, Ambient— 104510
Direct Chill, Countertop, Chilled, Hot— 104615
Direct Chill, Floorstanding, Chilled, Ambient, Hot— 104715
Direct Chill, Floorstanding, Chilled, Hot, Sparkling— 104810
Direct Chill, Floorstanding, Chilled, Ambient, Sparkling— 104815

Water system



Direct Chill Reservoir

Borg & Overström Direct Chill utilises innovative technology to chill water instantly. We recommend this system for more demanding environments because of its optimum dispense performance and unrivalled hygienic qualities. Superior to the gravity fed Reservoir system, Direct Chill technology chills water on demand for the ultimate drinking experience.



Phone
+44 (0)1362 695 006
Email
sales@borgandoverstrom.com

borgandoverstrom.com

Distributed by

Ref: 838102
Version: 02022016



A re-imagined classic

Built from the strong foundations set by the b2 range, this product boasts additional features including a larger dispense area, integrated cup dispenser and the option of sparkling water.



Key Features

- Touch panel button controls
- Auto lit dispense area
- Integrated cup dispenser
- Shrouded faucet for hygienic protection
- Floorstanding or countertop
- Available in direct chill or reservoir
- Chilled, ambient, hot and sparkling

Available accessories

- Waste Kit
- Leak Detection Kit
- Wall Bracket Set
- Cup Dispenser Blanking Plate
- Sparkling Refill (CO₂ E290)
- CO₂ Regulator with Gauge
- Sanitisation Kit
- Install Kit with Filter
- Waste Kit with Level Sensor
- Blue Tint Cups



Power requirements

Hertz 50/Volts 220-240
Max power consumption
Chilled & Ambient 100W
Chilled & Hot 545W

Chilled temperature

Chilled & Ambient Min 4°C/Max 11°C
Direct Chill Min 2°C/Max 11°C
Hot temperature
Max 92°C
Throughput litres per hour
Chilled 22/Hot 6

Dimensions

	WxDxH
Floorstanding	315x370x1065mm
Countertop	315x370x475mm
Dispense height	210mm