

borg&  
overström

f4



# Robust and simplistic

Where functionality and style merge,  
bringing a robust and timeless drinking  
solution to any environment.



<b>Power requirements</b>	<b>Chilled Temperature</b>	<b>Dimensions</b>	<b>WxDxH</b>
Hertz 50/Volts 240	Min 2°C/ Max 11°C	Floorstanding	360x270x1230mm
<b>Max power consumption</b>	<b>Throughput litres per hour</b>	Dispense height	220mm
120W	Chilled 40		

---

#### Key Features

- Robust stainless steel finish
- Direct Chill cooling system
- Up to 40 litres per hour output
- Simple to use and easy to maintain
- Solid construction

---

#### Available accessories

- Waste Kit
- Bottle Filler Blanking Plate
- Wall & Floor Bracket Set
- Waste Pump Kit
- Sanitisation Kit
- Install Kit with Filter
- Blue Tint Cups (7oz)



Water options




Chilled

Configuration



Floorstanding

Recommended environment



Industrial



Healthcare



Education



Leisure

Number of users



6 – 10



11 – 25



25+

f4 Models

Direct Chill, Floorstanding, Chilled - 401841

Water system



Direct Chill

Borg & Overström Direct Chill utilises innovative technology to chill water instantly. We recommend this system for more demanding environments because of its optimum dispense performance and unrivalled hygienic qualities. Superior to the gravity fed Reservoir system, Direct Chill technology chills water on demand for the ultimate drinking experience.

Phone  
+44 (0)1362 695 006  
Email  
sales@borgandoverstrom.com

[borgandoverstrom.com](http://borgandoverstrom.com)

Distributed by

Ref: 838134  
Version: 13012015