



STORM
POU Water Cooler

C & C

Our new Bottom-Load water dispenser – the Storm C&C, dispensing cold & ambient water – is the latest model in the Crystal Mountain's line of coolers. The Bottom-Load means no more lifting heavy bottles in any environment, just open the front door and the bottle slides into the base of the cooler with little effort. The Storm features an easy to remove reservoir system, that takes less than a minute to change. The LED indicator tells you when it needs to be replaced. Servicing has never been easier. With its contemporary design, attractive finish, concealed faucets and easy maintenance, the Storm is sure to dazzle in any environment.

Features

- High gloss finish, with stainless look and sliding front door
- Holds bottles sizes 11, 15 and 19 liters, 3,4, and 5 gallon bottles
- LED light over faucet area, LED – low water indicator light
- SmartFlo™ Water Cartridge – replacing is simple, quick and hygienic
- Ergonomic – higher dispense point
- Commercial grade and quality construction
- Large dispensing area for coffee pots and larger water bottles
- Can also be POU/mains-fed (order separate Storm POU conversion kit)





STORM C&C



Crystal Mountain Products Limited
 Fence House, Fence Avenue
 Macclesfield, Cheshire
 United Kingdom SK10 1LT
 Tel: +44(0) 1625 439 111
 Fax: +44 (0) 1625 502 527
 E-mail: cmeurope@crystalcoolers.com



SmartFlo™ Water Cartridge

Simple: In less than 45 seconds all water contact points are exchanged

Quick: In less than 45 seconds all water contact points are exchanged

Hygienic: All water contact points are exchanged

100% Sanitization



Concealed Water Outlet



Removable Drip Tray



Unique Sliding Front Door

Storm POU assembly



ITEM		SPECIFICATIONS
Power rating		Single phase 220-240VAC, 50Hz
Standard current		C&C: 1.0 ~1.2A
Power Consumption	Cold	70W
Cold	Compressor	Single phase motor
	Refrigerant	R600a
	Temp range	4-10°C (39.2 - 50°F)
	Temp control	Thermostat (ON 8±1.5°C, OFF 4°C±1.5°C)
Volume of Cold Reservoir		1.6L (0.4 gal)
Refrigerant charge		18g (0.63 oz)
Noise(sound power level)		Pump: 50dB(A); Compressor: 43dB(A)
Product weight		C&C: 14.0kg (31.0 lb)
Product boxed weight		C&C: 15.7kg (35.0 lb)
POU assembly weight		2.0kg (4.5 lb)
POU assembly boxed weight		2.6kg (5.7 lb)
Product dimensions		320(W) x 340(D) x 1116(H)mm 12.6"(W) X 13.4"(D) X 43.9"(H)
Product boxed dimensions		340(W) X 380(D) X 1165(H)mm 13.4" (W) X 15.0" (D) X 45.9" (H)
Loading quantity		20' Container: 204 Units 40' Container: 420 Units
IEC protection class		Class 1
Certifications		C-UL-US, CE, CB