

Refresh U 40 and 80 Small and efficient







Record-breaking compact design

These compact, high-performance coolers of the U40 and U80 series are remarkably small. Starting at just 19.5 cm wide, the U40 is still the smallest and most imitated cooler on the market. Their performance makes these coolers ideal for the home or small offices. Their size means that they are highly sought after when space is at a premium.

Always ready for use and practically maintenance free

Installation is simple thanks to the quick-fit connections that need no tools. Neither model requires preliminary filling of the tank or subsequent level checks. Moreover, the special sealed stainless steel cooling circuit does away with the need for periodic and costly sanitisation.

Compatible with a cartridge filtration system

Both the U40 and the larger high-performance U80 model can be connected to a cartridge filtration system.

Stainless steel refrigeration chamber

Both coolers have a Zerica-patented refrigeration chamber that uses the exclusive Silver Turbo Clean system which generates a water vortex on the internal walls whenever water is dispensed so preventing biofilm formation. In addition, the sealed stainless steel cooling chamber Is welded together using silver, a material well known for its antibacterial properties.

Carefully selected components

The entire system is made to a design that focuses on providing a very reliable cooler. For this reason the components have been carefully selected to guarantee maximum safety and hygiene. The evaporator is made entirely of stainless steel, with no plastic parts. The care taken with the whole design is also reflected in the noiseless running of the system at any stage of operation, making these coolers particularly suitable for installation in any domestic environment.

STANDARD ACCESSORIES

- stainless steel outer casing thermostat for regulating the water temperature OPTIONAL ACCESSORIES
- head for filter cartridge filter cartridge kit for connection to a cooler bottle to be independent of mains water











	U40	U80
UNDERSINK POSITION	✓	✓
DISPENSES COLD AND AMBIENT WATER	✓	✓
COOLING SYSTEM	SILVER TURBO CLEAN	SILVER TURBO CLEAN
*COOLING CAPACITY (Δt =4oC/ Δt =14oC)	28/8 l/h	33/9 l/h
'NO BACTERIA RISK' EVAPORATOR	✓	✓
STATIC COOLING	✓	✓
STAINLESS STEEL WATER CIRCUIT	✓	✓
LOW NOISE SYSTEM	✓	✓
STAINLESS STEEL OUTER CASING	✓	✓
COMPRESSOR POWER	1/15 HP	1/15 HP
COLD WATER THERMOSTAT	✓	✓
** AMPERE	0,6	0,6
NET WEIGHT (GROSS) - kg	10 (11)	11 (12)
DIMENSIONS (HxWxD) - cm	34,5 x 19,5 x 29	34,5 x 19,5 x 39



The quick-fit connections at the inlet take small gauge connecting pipes to simplify connection to the mains in more difficult conditions.

- NOT AVAILABLE STANDARD *THE VALUES SHOWN MAY VARY DEPENDING ON THE ENVIRONMENT AND USE OF THE PRODUCT. **VALUES REFER TO 230 V 50Hz - 20oC (± 10%)

