

Water options



Chilled

Ambient

Hot

Sparkling

Configuration



Countertop

Floorstanding

borg &
overström

b4

Recommended environment



Offices

Hospitality

Healthcare

Education

Leisure

Number of users



6–10

11–25

25+

b4 Models

Direct Chill, Countertop, Chilled, Ambient—103210
Direct Chill, Countertop, Chilled, Hot—103215
Direct Chill, Countertop, Chilled, Sparkling—103310
Direct Chill, Countertop, Chilled, Hot, Sparkling—103410
Base Cabinet—103910

Water system



Direct Chill

Borg & Overström Direct Chill utilises innovative technology to chill water instantly. We recommend this system for more demanding environments because of its optimum dispense performance and unrivalled hygienic qualities. Superior to the gravity fed Reservoir system, Direct Chill technology chills water on demand for the ultimate drinking experience.

Phone
+44 (0)1362 695 006
Email
sales@borgandoverstrom.com

borgandoverstrom.com

Distributed by

Ref: 838104
Version: 02022016



A design for flexibility

The range was created with an innate flexibility allowing it to flourish in all given environments – from boardroom to sports hall. Its compact size, large dispense and flexible water options position it as the premium solution.

Key Features

- Touch panel button controls
- Integrated cup dispenser (Floorstanding option only)
- High capacity, auto-lit dispense area
- Premium POU dispenser
- Floorstanding or countertop
- Chilled, ambient, hot and sparkling

Available accessories

- Sparkling Refill (CO₂ E290)
- CO₂ Regulator with Gauge
- Sanitisation Kit
- Install Kit with Filter
- Waste Kit with Level Sensor (Floorstanding option only)
- Blue Tint Cups



Power requirements

Hertz 50/Volts 220-240
Max power consumption
Chilled & Ambient 100W
Chilled & Hot 500W

Chilled temperature

Min 2°C/Max 11°C

Hot temperature

Max 92°C

Throughput litres per hour

Chilled 22/Hot 6

Dimensions

Floorstanding

Countertop

Internal

Dispense height

WxDxH

320x470x1325mm

320x470x415mm

208x355x835mm

265mm