

THE AA4400X POU WATER COOLER

“TOP OF THE RANGE” good looking and sturdily built, the AA4400X has made a name for itself for reliability, strength and performance.

The AA4400X uses modern Solenoid push button taps which light up on touch. A backlit logo panel enables you to show your own company logo in light.

An integral cup holder (floor standing units) avoids the need for unsightly add ons.

Typically taller than other Coolers, the dispensing taps are at a more ergonomic height.

Antimicrobial HygienGuard Technology inhibits bacterial growth where it matters most – at the dispensing point.

The AA4400X POU Water Cooler range – good looking sturdy and reliable performance...



AA
WATER COOLERS

THE AA4400X Series of POU Water Coolers

New HygieneGuard Tap Cover

The most critical hygiene area is undoubtedly the tap, which often gets contaminated through user hand contact (by comparison the "waterside" is much less critical). A silver impregnated plastic tap cover is designed to stop bacterial growth from contact contamination. The HygieneGuard tap cover can easily be replaced.

Cabinet

Cold-rolled 20 gauge embossed steel with baked on acrylic enamel finish

Drip Tray

Lift out design which can be connected to mains drainage, High impact durable plastic. Removable anti splash grid

Taps

Modern push and hold solenoid taps replace the old fashioned manual taps. The push and hold action prevents leaving the tap running by mistake whilst operating as a safety tap mechanism at the same time. The spouts of the solenoid taps are protected by the new HygieneGuard tap covers. Their silver impregnation is designed to prevent hand to tap bacterial contamination

Cup Holder

Integrated cup holder with exposed locking nuts to open up for easy refilling of cups

Removable Lower Front Panel

Spring loaded lower front panel. Remove drip tray and simply press down to remove entire lower front panel for easy access

Filters

POU Coolers are often fitted with a 1 micron nominal size Carbon Block Filter which removes the taste and smell of chlorine, a host of heavy metals/ chemicals and some pathogens which are unable to pass through the 1 micron nominal Carbon Block pore size

Refrigeration System

Quiet, air cooled static-type condenser. No fan required. Protected against motor overload. Unit hermetically sealed. R-134a refrigerant

Cooling System

Stainless Steel 3 litre cold water tank. Thermostatically controlled to 4C - 12C

Heating System

Stainless Steel 2 litre tank. Thermostatically controlled to between 87 and 92°C.

Designed to prevent total drainage for heating element protection. Easily accessible hot water tank drain at the back of the Cooler

Power Supply

220 Volt, 50/60 Hz. Provided with a 3 pin plug and 180 cm power cord

Dimensions

Floor Standing:	Height	1135mm
	Width	340mm
	Depth	340mm
Table Top:	Height	460mm
	Width	340mm
	Depth	340mm

Shipping Weights

Floor Standing:	18kg
Table Top:	15kg

Anthracite Finish:

WCPC 4400X	Floor Standing, Cook & Cold
WCPH 4400X	Floor Standing, Hot & Cold
WCPTC 4400X	Table Top, Cook & Cold
WCPTH 4400X	Table Top, Hot & Cold
WCPCSIP 4400X	SIP Self Sanitisation, Floor Standing, Cook & Cold
WCPSIP 4400X	SIP Self Sanitisation, Floor Standing, Hot & Cold
CONKIT 3300XB	Conversion Kit to Bottled



Your Local Distributor is