# CRYSTAL NOUNTAIN PRODUCT BROCHURE





**AVALANCHE** POU Water Cooler

# **AVALANCHE** POU Water Cooler

The small footprint Avalanche water cooler is designed to fit conveniently on a kitchen or office countertop. The compressor in this compact design provides exceptional cooling rates and runs very quietly. This Avalanche is available as Cold and Cold, or Hot and Cold, and has handy LED lights indicating when water reaches temperature.



## **Features and Benefits**

- Carrying handle makes dispenser easy to carry
- LED display indicates when cold and hot water are at the optimum temperature
- Small footprint conveniently fits kitchen or office
- Compressor operated for efficient water temperature recovery
- One piece drip tray is dishwasher safe



Carrying handle



LED display



## **Performance and Specifications**

#### General

Air cooled, POU type water cooler provided with a power supply cord for connection to source of power supply

#### **Cooler Cabinet**

Blow moulded, high density polyethylene (HDPE) Together with injunction moulded bottom plate

Available in white or black colour

#### **Faucet Type**

Constructed of FDA approved nylon and silicon tubing Polypropylene (PP) faucet with self closing handle

#### **Cold Water Tank Specifications**

HDPE casing with 1.1L (0.3 gal) volume

Cold water cooling capacity of 2.0L/hr (0.5 gal/hr) based on 21°C (69.8°F) room temperature

#### **Cold Water Thermostat**

Preset at factory to dispense water at temperature from  $4-10^{\circ}C$  (39.2- $50^{\circ}F$ ) Adjustable cold control located at the back of the cabinet

#### Hot Water Tank Specifications

Stainless steel #304 casing with 1.5L (0.4 gal) volume

Hot tank capacity 4.5L/hr (1.2 gal/hr) based on 21°C (69.8°F) room temperature

#### Hot Water Thermostats and Heater

Automatic thermostat set at temperature range of 74-92°C (165.2-197.6°F)

Manual thermostat reset in case of automatic thermostat failure

ON/OFF switch for hot tank is located at the back of the cabinet

#### Compressor

Hermetically sealed reciprocating compressor (220~240VAC 50Hz) **Refrigerant Type:** R600a (CFC Free)

Refrigerant Charge: 12.0g (0.42 oz)



### **Dimensions and Freight Data**

Model	Products Dimensions WxDxH (mm/in.)	Box Dimensions WxDxH (mm/in.)	Product Weight (kg/lb)	Product Boxed Weight (kg/lb)	Loading Qty	
					20FT	40FT
Avalanche POU Water Cooler	368x330x419mm	380x370x450mm	H&C: 11.6kg (25.6 lb)	H&C: 12.6kg (27.7 lb)		960 units
	14.5"x13.0"x16.5"	15.0"x14.6"x17.7"	C&C: 10.9kg (24.0 lb)	C&C: 11.8kg (26.0 lb)		
			Cold Only: 10.3kg (22.7 lb)	Cold Only: 11.6kg (25.6 lb)		

All performances are tested in a controlled environment, certified by a third party. To learn more about these standards, please speak to your Crystal Mountain representative.



#### **Crystal Mountain Products Limited**

#### European Sales Office

Fence House, Fence Avenue Macclesfield, Cheshire United Kingdom SK10 1LT Tel: +44(0) 1625 439 111 Fax: +44 (0) 1625 502 527 E-mail: cmeurope@crystalcoolers.com

#### North American Sales Office

200 Carnegie Drive, Suite 234 St. Albert, AB, T8N 5A7 Canada Toll Free: 800 878 6422 Tel: 1 780 454 4545 E-mail: sales@crystalcoolers.com

#### **Crystal Mountain Products Inc.**

US Office / Warehouse 1000 H Taylor Station Rd Gahanna OH 43230 Tel: (614) 454 1618 Fax:(614) 409 9782 E-mail: sales@crystalcoolers.com

#### **Crystal Mountain International Limited**

#### Hong Kong Sales Office

Room 610, Winfield Commercial Building 6-8a Prat Avenue, Tsimshatsui Kowloon, Hong Kong Tel: (852) 2368 1989 Fax: (852) 3017 6727 E-mail: cmasia@crystalcoolers.com



## CE COULUS LISTED CB C SASO ISO9001 WEEE ROHS

## Website: www.crystalcoolers.com

Crystal Mountain has a policy of continuous development and reserves the right to change specifications without notification.

