

ArcticChill 88

Exceptional Capacity

Delivers 30 - 40 Litres
Per Hour Of Chilled
Water Below 12°C

23cm Dispensing
Height To Fill
Bottles



AAFIRST
WATER COOLERS
& BOILERS



- Direct chill cold water cooler
- Single dispensing button for Chilled water
- Can be fitted with overflow kits & mains drainage
- Fits our standard coving and wall Bracket
- WRAS approved
- FloodGuard inlet solenoid protects the cooler against large scale flooding
- Impressive 23cm dispensing height

refreshingly different

ArcticChill 88

Exceptional Capacity

Accessories For The ArcticChill 88

Filter Housing With Carbon Block Candle & Nanofilter.



Installation Rail With Filter. Includes Compression Fitting, 1-Micron Green Filter, Water Block, Copper Pressure Reducing Valve & Non-Return Valve.



A Pumped Main Drainage System Pumps The Waste Water From The Drip Tray Over A Distance Of 100m & A Rise Of 5m. (Factory Installed).



FloodGuard - Inlet Solenoid Only Opens To Allow Water Into The Cooler, When Water Is Dispensed. By Remaining Closed All Other Times It Protects The Cooler Against Leaks.



Cowling To Fix The Cooler Securely To The Wall (Supplied Separately).



Mains Drainage - Connect The Drip Tray To Mains Drainage. Can Be Supplied With A Pump, To Pump The Water Over 50m & A Rise Of 5m.



3 Litre Overflow Kit Connects The Drip Tray To A 3 Litre Alarmed Overflow Container. The Container Has A Tap To Empty Without Removing It.



10 Litre Overflow System With Alarm To Signal When Full. (Factory Fitted).



Description	Dimensions H x W x D mm	Weight (Kg)
POU Floor Standing	1135 x 340 x 340	25
POU Table Top	460 x 340 x 340	16

Local Distributor

AAFIRST
WATER COOLERS
& BOILERS

www.aafirst.co.uk